

## MPF PRODUCTS INC.





## NOTES:

- 1. MATERIAL: CaF2
- 2. SURFACE FINISH: 40/20 SCRATCH-DIG
- 3. PARALLELISM: < 3 ÅRC MINUTES
- 4. FLATNESS: 2 WAVES @ 633nm
- 5. THERMAL RANGE: -100°C TO 200°C
- 6. LEAK RATE < 2X10^-10 ATM CC/SEC HE

Calcium Fluoride (CaF2) Viewport, UHV Rated Vacuum Optics, 0.40" View Dia, 1.33" Conflat Flange

UNLESS OTHERWISE SPECIFIED:	QUOTATION #				APPROVED		
DIMENSIONS ARE IN INCHES TOLERANCES:	DATE TO THE PARTY OF THE PARTY			1			
		NAME	DATE		MPF PRODUCTS INC		
	DRAWN	W٦	11/14/2015	I IV			
ANGULAR: MACH ± 1/2° TWO PLACE DECIMAL	CHECKED	MJ	11/14/2015	TITL	E:		
	ENG APPR.	W٦	11/14/2015				
THREE PLACE DECIMAL ± .015	THIRD ANGLE:			Ī	VIEWPORT, CaF2,		
				VAC-OPTICS, 0.40" VIEW, 133CF			
MATERIAL							
	APPLICATION			1			
	NEXT ASSY	USED ON		_			
				DOV	DOWNLOADED FROM MPFPI.COM		
FINISH	SURFACE FINIS	SH:	OR BETTER	DWC	G. NO.	REV	
CONFLAT	UNLESS OTHERWISE SPECIFIED:		A14347-1-CF				
PLATING	ALL DIAMETERS CONCENTRIC WITHIN .005. REMOVE ALL BURRS AND SHARP EDGES				/ (1 <del>1 0 1</del> / 1 C1		
-				Wednesday, November 25, 2015 8:19:00 AM			

SHEET 1 OF 1