SHEET 1 OF 2 SHEETS

A11563

REV

1	MA	тг	עום	1.0	٠.	
ı	IVIA	۱Г	⋉୲୵	٠I.) .	

CONTACTS: BERYLLIUM-COPPER ALLOY 172/173 IN ACCORDANCE WITH ASTM B196/197.

DIELECTRIC: CERAMAX PROPRIETARY CERAMIC.

SHELL: STAINLESS STEEL ALLOY 304L IN ACCORDANCE WITH SAE AMS-QQ-S-763.

2. FINISH:

CONTACTS: NICKEL PLATE PER QQ-N-290, .000100/ .000250 THICK. GOLD PLATE PER ASTM B488-01, TYPE II, CODE C, .000050/ .000100 THICK.

3. DOUBLE-ENDED (STANDARD FEMALE RECEPTACLE/CUSTOM RECEPTACLE) CONFIGURATION WITH THE WELD INTERFACE AT THE TOP AMBIENT INTERFACE CONFORMS TO MIL-DTL-83513/2 (MPF PART # A9602) VACUUM INTERFACE MATES WITH CONNECTOR A9601

INCORPORATES BERYLLIUM-COPPER CONTACTS INDIVIDUALLY SEALED TO ESTABLISH A DURABLE HERMETIC SEAL.

PART #	# OF PINS	FLANGE SIZE
A11563-1-CF	9	2.75 CF
A11563-2-CF	15	2.75 CF
A11563-3-CF	21	2.75 CF
A11563-4-CF	25	2.75 CF
A11563-5-CF	31	2.75 CF
A11563-6-CF	37	2.75 CF
A11563-7-CF	51	2.75 CF
A11563-8-CF	100	4.50 CF

^{*} CONFIGURATIONS SHOWN ON PAGE 2

APPROVED


MULTIPIN, MICRO-D, 300V, 10A

TITLE:


Micro-D type Multipin Feedthrough, 9,15,21,25,31,37,51, and 100 Pins, 300 Volts, 10 Amps per pin 2.75" & 4.50" Conflat Flange

PROPRIETARY AND CONFIDENTIAL UNLESS OTHERWISE SPECIFIED: MPF PRODUCTS INC.							9,15,21,25,31,37,51, AND 100 PIN 275CF & 450CF			
ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF MPF PRODUCTS INC. IS PROHIBITED. USED ON:	DIMENSIONS ARE IN INCHES TOLERANCES:	(0)	FINISH CF FLANGE	DRAWN BY	JB	DATE	SIZE	DWG.	NO. A11563	REV
USED ON.	ANGULAR: MACH ± 1/2 °	9 7	OI ILANOL	CHECKED						
	TWO PLACE DECIMAL THREE PLACE DECIMAL	±.030 ±.015	DO NOT SCALE DRAWING	ENG APPR.	JB		LAST SA	VED DATE	Friday, May 03, 2013 8:43:19 AM	


SHEET 2 OF 2 SHEETS REV A11563 5/3/2013 A11563-5-CF









A11563-2-CF




A11563-3-CF




A11563-4-CF



A11563-6-CF



A11563-7-CF



A11563-8-CF

APPROVED

MULTIPIN, MICRO-D, 300V, 10A

TITLE:

Micro-D type Multipin Feedthrough, 9,15,21,25,31,37,51, and 100 Pins, 300 Volts, 10 Amps per pin 2.75" & 4.50" Conflat Flange

PROPRIETARY AND CONFIDENTIAL	PROPRIETARY AND CONFIDENTIAL UNLESS OTHERWISE SPECIFIED: MPF PRODUCTS INC.						9,15,21,25,31,37,51, AND 100 PIN 275CF & 450CF			
ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF MPF PRODUCTS INC. IS PROHIBITED. USED ON:	DIMENSIONS ARE IN INCHES TOLERANCES:	(+) [-]	FINISH CF FLANGE	DRAWN BY		DATE	SIZE	DWG.	NO. A11563	REV
USED ON:	ANGULAR: MACH ± 1/2°	9	CITEAROL	CHECKED						5/3/2013
	TWO PLACE DECIMAL THREE PLACE DECIMAL	±.030 ±.015	DO NOT SCALE DRAWING	ENG APPR.			LAST SA	VED DATE	Friday, May 03, 2013 8:43:19 AM	