


A4863

REV

11/19/2013



PART #	LENGTH
A4863-1-CN	10"
A4863-2-CN	30"
A4863-3-CN	12"
A4863-4-CN	24"
A4863-5-CN	36"

RATINGS:

1. IMPEDANCE: 50 OHMS
2. DIELECTRIC WITHSTANDING VOLTAGE: 1000V RMS AT SEA LEVEL
3. CONTACT RESISTANCE: 3 MILLIOHMS MAX D.C.
4. CURRENT CAPACITY: 3 AMPS D.C.
5. INSULATION RESISTANCE: 5 X 10⁽⁻³⁾ MEGAOHMS MIN. AT 500V D.C.
6. VSWR: 1.2 MAX - 2 GHZ
7. TEMPERATURE RATING: -62 °C TO 150 °C

APPROVED

TITLE:

**MICRODOT TO MICRODOT
VACUUM SIDE CABLE**

PROPRIETARY AND CONFIDENTIAL

UNLESS OTHERWISE SPECIFIED:

MPF PRODUCTS INC.

ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE
WRITTEN PERMISSION OF MPF PRODUCTS INC. IS PROHIBITED.

NEXT ASSEMBLY USED ON

DIMENSIONS ARE IN INCHES
TOLERANCES:

ANGULAR: MACH ± 1/2 °
TWO PLACE DECIMAL ±.030
THREE PLACE DECIMAL ±.015



FINISH
CABLE ASSEMBLY

DO NOT SCALE DRAWING

DRAWN BY

CHECKED

ENG APPR.

JB

GS

JB

DATE

11/19/2013

11/19/2013

SIZE

A

DWG. NO.

A4863

REV

11/19/2013

LAST SAVED DATE

Tuesday, November 19, 2013 12:54:25 PM