



Specifications

Sealing Mechanism: Welded Bellows
Material Exposed to Vacuum: Stainless Steel (Bellows)
Bellows ID: 1.25" (31.8mm)
Bakeout Temperature: 200°C (Micrometers removed)
Operating Temp: -20° to 100°C


Pressure Range: Atmosphere To 1 x 10⁻¹¹ Torr
(Bellows model)
Operating Load: 50 lbs.
Micrometer: Motion: +/- 12.5 mm or .5"
Resolution: .002 mm or .0001"
Flanges: Tapped, 1/4"-28

THIS DRAWING IS THE PROPERTY OF HUNTINGTON MECHANICAL LABS, INC., AND IS PROPRIETARY IN GENERAL AND IN DETAIL. IT SHALL NOT BE MODIFIED IN ANY WAY. PERMISSION IS GIVEN TO PRINT AND DISSEMINATE FREELY.

This model can be motorized, please call for quote



2-3/4" VAC-U-FLANGE® (CF)



DESCRIPTION	WEIGHT (lbs.)	PART NUMBER
Metric micrometer driven X-Y Manipulator without Bellows	7.0	TS-275
Metric micrometer driven X-Y Manipulator, Tapped Flanges, with Bellows	7.5	TS-275-155

Other options available. For quotes, please call 800-227-8059 or visit our website at www.huntvac.com. Email: vacman@huntvac.com

 Huntington Mechanical Labs, Inc.		13355 NEVADA CITY AVENUE GRASS VALLEY, CA. 95945	
MANIPULATOR, X-Y AXIS, MICROMETER, .002mm RES.			
B	DWG. NO.	TS-275(-XXX) OUTLINE	REV. B
SCALE: NO SCALE		SHEET: 1	OF 1